



ECUADOR

PANAMA

1700 ECUATEPI
3 2 8 2 8 3 7 4

Sitio web: www.ecuatepi.com

E- Mail: info@ecuatepi.com



Wheeled Dry Chemical

With our comprehensive line, Buckeye Wheeled Dry Chemical fire extinguishers have your large-scale fire protection needs covered. Available in three size capacities with three choices of extinguishing agent and three different operational design configurations, the best match for your hazard protection needs can be accurately selected, maximizing the fire safety of your operation.

Designed for one man operation these units are easily transportable through doorways and over rough terrain. Tow Loops can be added to your selection if you need easy vehicle transport capability.

All models are rechargeable and meet relevant UL, ULC, TC & DOT requirements. Selected models have US Coast Guard Approval.

Stationary models are also available. **Typical Uses:** Offshore rigs, ship docks, refineries, chemical plants, aircraft ramps, remote construction sites, large laboratories, processing plants, storage and loading areas. Not for use on sensitive electronic equipment.

Dry chemical wheeled units are available for Class A, Class B and Class C fires.



TECNICAS ECUATORIANAS DE PROTECCIÓN CONTRA INCENDIOS

ECUATEPI S.A.

Pag. 1





ECUADOR

PANAMA

1700 ECUATEPI
3 2 8 2 8 3 7 4

Sitio web: www.ecuatepi.com

E- Mail: info@ecuatepi.com



Wheeled Dry Chemical - Product Specification

UNIT HEIGHT	UNIT WIDTH	UNIT DEPTH	HOSE LENGTH & DIAMETER	WHEEL TYPE	WHEEL DIAMETER
47 inches (119 cm)	24 inches (61 cm)	26.5 inches (67 cm)	25 ft. x 50 in. (7.6 m x 1.3 cm)	Rubber	22.3 in. x 3.5 in. (51.3 cm x 8.9 cm)
51 inches (128 cm)	26 inches (66 cm)	38 inches (96.5 cm)	50 ft. x 75 in. (15.2 m x 1.9 cm)	Rubber	16 in. x 4 in. (40.6 cm x 10.2 cm)
50 inches (127 cm)	24 inches (61 cm)	42 inches (105 cm)	50 ft. x 75 in. (15.2 m x 1.9 cm)	Rubber	16 in. x 4 in. (40.6 cm x 10.2 cm)
55 inches (139 cm)	32 inches (81.3 cm)	46 inches (117 cm)	50 ft. x 75 in. (15.2 m x 1.9 cm)	Steel	36 in. x 2.5 in. (91.4 cm x 6.4 cm)
55 inches (139 cm)	32 inches (81.3 cm)	46 inches (117 cm)	50 ft. x 75 in. (15.2 m x 1.9 cm)	Steel with rubber tread	36 in. x 2.5 in. (91.4 cm x 6.4 cm)
50 inches (127 cm)	24 inches (61 cm)	42 inches (105 cm)	50 ft. x 75 in. (15.2 m x 1.9 cm)	Rubber	16 in. x 4 in. (40.6 cm x 10.2 cm)
58 inches (147 cm)	36 inches (91.4 cm)	48 inches (122 cm)	50 ft. x 1 in. (15.2 m x 2.5 cm)	Steel	36 in. x 6 in. (91.4 cm x 15.2 cm)
58 inches (147 cm)	36 inches (91.4 cm)	48 inches (122 cm)	50 ft. x 1 in. (15.2 m x 2.5 cm)	Steel with rubber tread	36 in. x 6 in. (91.4 cm x 15.2 cm)
58 inches (147 cm)	36 inches (91.4 cm)	48 inches (122 cm)	50 ft. x 1 in. (15.2 m x 2.5 cm)	Steel	36 in. x 6 in. (91.4 cm x 15.2 cm)
58 inches (147 cm)	36 inches (91.4 cm)	48 inches (122 cm)	50 ft. x 1 in. (15.2 m x 2.5 cm)	Steel with rubber tread	36 in. x 6 in. (91.4 cm x 15.2 cm)
50 inches (127 cm)	24 inches (61 cm)	42 inches (105 cm)	50 ft. x 75 in. (15.2 m x 1.9 cm)	Rubber	16 in. x 4 in. (40.6 cm x 10.2 cm)
55 inches (139 cm)	32 inches (81.3 cm)	46 inches (117 cm)	50 ft. x 75 in. (15.2 m x 1.9 cm)	Steel	36 in. x 2.5 in. (91.4 cm x 6.4 cm)
55 inches (139 cm)	32 inches (81.3 cm)	46 inches (117 cm)	50 ft. x 75 in. (15.2 m x 1.9 cm)	Steel with rubber tread	36 in. x 2.5 in. (91.4 cm x 6.4 cm)
50 inches (127 cm)	24 inches (61 cm)	42 inches (105 cm)	50 ft. x 75 in. (15.2 m x 1.9 cm)	Rubber	16 in. x 4 in. (40.6 cm x 10.2 cm)
58 inches (147 cm)	36 inches (91.4 cm)	48 inches (122 cm)	50 ft. x 1 in. (15.2 m x 2.5 cm)	Steel	36 in. x 6 in. (91.4 cm x 15.2 cm)
58 inches (147 cm)	36 inches (91.4 cm)	48 inches (122 cm)	50 ft. x 1 in. (15.2 m x 2.5 cm)	Steel with rubber tread	36 in. x 6 in. (91.4 cm x 15.2 cm)
58 inches (147 cm)	36 inches (91.4 cm)	48 inches (122 cm)	50 ft. x 1 in. (15.2 m x 2.5 cm)	Steel	36 in. x 6 in. (91.4 cm x 15.2 cm)
58 inches (147 cm)	36 inches (91.4 cm)	48 inches (122 cm)	50 ft. x 1 in. (15.2 m x 2.5 cm)	Steel with rubber tread	36 in. x 6 in. (91.4 cm x 15.2 cm)
47 inches (119 cm)	24 inches (61 cm)	26.5 inches (67 cm)	25 ft. x 50 in. (7.6 m x 1.3 cm)	Rubber	22.3 in. x 3.5 in. (51.3 cm x 8.9 cm)
51 inches (128 cm)	26 inches (66 cm)	38 inches (96.5 cm)	50 ft. x 75 in. (15.2 m x 1.9 cm)	Rubber	16 in. x 4 in. (40.6 cm x 10.2 cm)
50 inches (127 cm)	24 inches (61 cm)	42 inches (105 cm)	50 ft. x 75 in. (15.2 m x 1.9 cm)	Rubber	16 in. x 4 in. (40.6 cm x 10.2 cm)
55 inches (139 cm)	32 inches (81.3 cm)	46 inches (117 cm)	50 ft. x 75 in. (15.2 m x 1.9 cm)	Steel	36 in. x 2.5 in. (91.4 cm x 6.4 cm)
55 inches (139 cm)	32 inches (81.3 cm)	46 inches (117 cm)	50 ft. x 75 in. (15.2 m x 1.9 cm)	Steel with rubber tread	36 in. x 2.5 in. (91.4 cm x 6.4 cm)
50 inches (127 cm)	24 inches (61 cm)	42 inches (105 cm)	50 ft. x 75 in. (15.2 m x 1.9 cm)	Rubber	16 in. x 4 in. (40.6 cm x 10.2 cm)
58 inches (147 cm)	36 inches (91.4 cm)	48 inches (122 cm)	50 ft. x 1 in. (15.2 m x 2.5 cm)	Steel	36 in. x 6 in. (91.4 cm x 15.2 cm)
58 inches (147 cm)	36 inches (91.4 cm)	48 inches (122 cm)	50 ft. x 1 in. (15.2 m x 2.5 cm)	Steel with rubber tread	36 in. x 6 in. (91.4 cm x 15.2 cm)
58 inches (147 cm)	36 inches (91.4 cm)	48 inches (122 cm)	50 ft. x 1 in. (15.2 m x 2.5 cm)	Steel	36 in. x 6 in. (91.4 cm x 15.2 cm)
58 inches (147 cm)	36 inches (91.4 cm)	48 inches (122 cm)	50 ft. x 1 in. (15.2 m x 2.5 cm)	Steel with rubber tread	36 in. x 6 in. (91.4 cm x 15.2 cm)

Operating Temperature Range for all wheeled dry chemical extinguishers is -65° to 120°F (-54° to 49°C).

TECNICAS ECUATORIANAS DE PROTECCIÓN CONTRA INCENDIOS

ECUATEPI S.A.

Pag. 2





ECUADOR

PANAMA

1700 ECUATEPI
3 2 8 2 8 3 7 4

Sitio web: www.ecuatepi.com

E- Mail: info@ecuatepi.com



Wheeled Dry Chemical - Product Specification

SP - Stored Pressure RG - Regulated Pressure PT - Pressure Transfer
Canadian Part Numbers are shown in parentheses.

MODEL	TYPE	PART NUMBER	AGENT CAPACITY	UL / IBC RATING	DISCHARGE TIME	DISCHARGE RANGE	UNIT WEIGHT
A-50-SP	ABC Dry Chemical	30010 (30015)	50 lb (22.7 kg)	1-0-A-160-B-C	35 sec	25-35 ft. (7.6-10.7 m)	154 lb (70 kg)
A-150-SP	ABC Dry Chemical	30110 (30115)	125 lb (56.7 kg)	3-0-A-240-B-C	47 sec	30-40 ft. (9.1-12.2 m)	300 lb (136 kg)
A-150-RG	ABC Dry Chemical	31130 (31135)	125 lb (56.7 kg)	3-0-A-240-B-C	44 sec	30-40 ft. (9.1-12.2 m)	307 lb (139 kg)
A-150-RG-36	ABC Dry Chemical	31140 (31145)	125 lb (56.7 kg)	3-0-A-240-B-C	44 sec	30-40 ft. (9.1-12.2 m)	422 lb (191 kg)
A-150-RG-36R	ABC Dry Chemical	31150 (31155)	125 lb (56.7 kg)	3-0-A-240-B-C	44 sec	30-40 ft. (9.1-12.2 m)	430 lb (197 kg)
A-150-PT	ABC Dry Chemical	31120 (31125)	125 lb (56.7 kg)	3-0-A-240-B-C	45 sec	30-40 ft. (9.1-12.2 m)	325 lb (147 kg)
A-350-RG	ABC Dry Chemical	32120 (32125)	300 lb (136 kg)	3-0-A-320-B-C	52 sec	30-40 ft. (9.1-12.2 m)	780 lb (354 kg)
A-350-RG-R	ABC Dry Chemical	32140 (32145)	300 lb (136 kg)	3-0-A-320-B-C	52 sec	30-40 ft. (9.1-12.2 m)	806 lb (366 kg)
A-350-PT	ABC Dry Chemical	32110 (32115)	300 lb (136 kg)	3-0-A-320-B-C	53 sec	30-40 ft. (9.1-12.2 m)	657 lb (298 kg)
A-350-PT-R	ABC Dry Chemical	32130 (32135)	300 lb (136 kg)	3-0-A-320-B-C	53 sec	30-40 ft. (9.1-12.2 m)	683 lb (310 kg)
S-150-RG	Standard Dry Chemical	31220 (31225)	150 lb (68 kg)	240-B-C	48 sec	30-40 ft. (9.1-12.2 m)	412 lb (187 kg)
S-150-RG-36	Standard Dry Chemical	31240 (31245)	150 lb (68 kg)	240-B-C	48 sec	30-40 ft. (9.1-12.2 m)	447 lb (203 kg)
S-150-RG-36R	Standard Dry Chemical	31250 (31255)	150 lb (68 kg)	240-B-C	48 sec	30-40 ft. (9.1-12.2 m)	459 lb (208 kg)
S-150-PT	Standard Dry Chemical	31210 (31215)	150 lb (68 kg)	240-B-C	43 sec	30-40 ft. (9.1-12.2 m)	350 lb (159 kg)
S-350-RG	Standard Dry Chemical	32220 (32225)	350 lb (159 kg)	320-B-C	59 sec	30-40 ft. (9.1-12.2 m)	830 lb (376 kg)
S-350-RG-R	Standard Dry Chemical	32240 (32245)	350 lb (159 kg)	320-B-C	59 sec	30-40 ft. (9.1-12.2 m)	856 lb (388 kg)
S-350-PT	Standard Dry Chemical	32210 (32215)	350 lb (159 kg)	320-B-C	59 sec	30-40 ft. (9.1-12.2 m)	707 lb (321 kg)
S-350-PT-R	Standard Dry Chemical	32230 (32235)	350 lb (159 kg)	320-B-C	59 sec	30-40 ft. (9.1-12.2 m)	733 lb (333 kg)
K-50-SP	Purple K Dry Chemical	30030 (30035)	50 lb (22.7 kg)	160-B-C	34 sec	25-35 ft. (7.6-10.7 m)	154 lb (70 kg)
K-150-SP	Purple K Dry Chemical	30130 (30135)	125 lb (56.7 kg)	320-B-C	54 sec	30-40 ft. (9.1-12.2 m)	300 lb (136 kg)
K-150-RG	Purple K Dry Chemical	31150 (31155)	125 lb (56.7 kg)	320-B-C	55 sec	30-40 ft. (9.1-12.2 m)	307 lb (139 kg)
K-150-RG-36	Purple K Dry Chemical	31140 (31145)	125 lb (56.7 kg)	320-B-C	55 sec	30-40 ft. (9.1-12.2 m)	422 lb (191 kg)
K-150-RG-36R	Purple K Dry Chemical	31150 (31155)	125 lb (56.7 kg)	320-B-C	55 sec	30-40 ft. (9.1-12.2 m)	430 lb (197 kg)
K-150-PT	Purple K Dry Chemical	31120 (31125)	125 lb (56.7 kg)	320-B-C	54 sec	30-40 ft. (9.1-12.2 m)	325 lb (147 kg)
K-350-RG	Purple K Dry Chemical	32120 (32125)	300 lb (136 kg)	320-B-C	57 sec	30-40 ft. (9.1-12.2 m)	780 lb (354 kg)
K-350-RG-R	Purple K Dry Chemical	32140 (32145)	300 lb (136 kg)	320-B-C	57 sec	30-40 ft. (9.1-12.2 m)	806 lb (366 kg)
K-350-PT	Purple K Dry Chemical	32110 (32115)	300 lb (136 kg)	320-B-C	62 sec	30-40 ft. (9.1-12.2 m)	657 lb (298 kg)
K-350-PT-R	Purple K Dry Chemical	32130 (32135)	300 lb (136 kg)	320-B-C	62 sec	30-40 ft. (9.1-12.2 m)	683 lb (310 kg)

US Coast Guard Approved Models - Part numbers 30010, 30110, 30030, 30310 & 31210

TECNICAS ECUATORIANAS DE PROTECCIÓN CONTRA INCENDIOS

ECUATEPI S.A.

Pag. 3

