



PORTABLE FIRE EXTINGUISHERS

5 LB. CARBON DIOXIDE STORED PRESSURE FIRE EXTINGUISHER

DESCRIPTION

Buckeye's 5 LB Carbon Dioxide Fire extinguisher is used on "B" and "C" class fires.

It is ideal for use in chemical and manufacturing plants, oil rigs, rail yards, warehouses, construction sites, parking garages, boat docks, and large laboratories. Because CO₂ is residue free it is recommended for use on sensitive electronic equipment such as computers, control panels, electrical boxes, etc.

FEATURES

- Manufactured in accordance with ANSI/UL 154 and ANSI/UL 711 Standards. USDOT compliant cylinders are tested to 3000 psi.
- US COAST GUARD approved for Type B:C Size I when used in conjunction with Mounting Bracket Model 809, P/N 700226.
- Polyester epoxy powder coated aluminum cylinder, rugged plated brass valve, and stainless steel handle and lever.
- Carbon Dioxide is a residue-free extinguishing agent that is environmentally friendly. Carbon Dioxide has an Ozone Depletion Potential (ODP) of 0 and a Global Warming Potential (GWP) of 1.

SPECIFICATIONS

Agent Capacity: 5 lbs. / 2.27 kg

UL Rating: 5-B:C

Shipping Weight: 13.75 lbs. / 6.3 kg

Height: 17.375 in / 44.1 cm

Width: 8.25 in / 21 cm

Cylinder Diameter: 5.25 in / 13.3 cm

Discharge Time: 9 seconds

Discharge Range: 4 – 8 ft / 1.2 – 2.4 m

Operating Temperature Range:
-22° F to 120° F / -30° C to 49° C

ORDERING INFORMATION

**5 LB Carbon Dioxide Fire Extinguisher
with Wall Hook**
P/N 45100

Note: For Coast Guard Approval you must also order the Model 809 Mounting Bracket, P/N 700226

Refer to the Buckeye Spare Parts List for replacement parts