



ECUATEPI S.A.

DATASHEET

**FIRE
ENGINEERING**

EXTINGUISHERS



Wheeled Carbon Dioxide

Our Wheeled Carbon Dioxide extinguishers are designed for one-man operation and are constructed with spun steel cylinders and plated brass valve assemblies. DOT/TC approved cylinders, rugged frames and solid rubber tires are key features of these UL/ULC approved units.

Carbon Dioxide is a residue-free agent and is suitable for use on Class B and Class C fires.

Typical Uses: For protecting sensitive electronic equipment in refineries, shipboard, laboratories, construction sites, chemical plants and manufacturing facilities.

Third Party Approvals For Peace Of Mind



Model	C-50-SE	C-100-SE
Part #	35050 (35091)	35100 (35191)
Agent Capacity	50 lb. (22.68 kg)	100 lb. (45.36 kg)
UL Rating	20-B:C	20-B:C
USCG Approval	Type B:C Size IV	Type B:C Size V
Operating Temperature Range	-22° to 120°F (-30° to 49°C)	-22° to 120°F (-30° to 49°C)
Discharge Time	40 sec	80 sec
Range	15 ft. (4.6 m)	15 ft. (4.6 m)
Unit Weight	286 lb. (130 kg)	416 lb. (189 kg)
Unit Height x Width x Depth	60" x 31" x 21" (152.4 x 76.2 x 53.3 cm)	65" x 30" x 21" (165.1 x 76.2 x 53.3 cm)
Hose Diameter & Length	.50 in x 15 ft. (1.27 cm x 4.6 m)	.50 in x 40 ft. (1.27 cm x 12.2 m)



Manuel Larrea N17-241 y Santiago
Telefax: 02 222-9444 / Cell: 0987178263
Email: info@ecuatepi.com